How to change or transform a coordinate system into a map layer? The answer is in ArcMap.

Anabela Grifo^{(1,2)*}, Albertina Ferreira^(1,6)

⁽¹⁾ Departamento de Ciências Agrárias e Ambiente– Escola Superior Agrária - Instituto Politécnico de Santarém, <u>anabela.grifo@esa.ipsantarem.pt; albertina.ferreira@esa.ipsantarem.pt</u>

⁽²⁾ Instituto de Ciências Agrárias e Ambientais Mediterrâneas-ICAAM, Universidade de Évora. ⁽⁶⁾ Centro Interdisciplinar de História, Culturas e Sociedades da Universidade de Évora – CIDEHUS,

Abstract

The application of new technologies to agricultural activity, associated with the Global Positioning System, generates high amount of georeferenced information. Thus, we are often confronted with different assignments of coordinate systems. The transformation of data from one source of information into the data coordinate system from another source is a prior and fundamental step to any analysis of georeferenced information.

This study aims to know and understand the transformation process of geographical coordinates into rectangular ones and vice versa, as well as the transformation between different coordinate systems, through the ArcMap software tools because it is a question often asked by students and others who try to use the Geographic Information Systems tools.

Keywords: georeferenced information, transformation coordinate systems, precision agriculture

Resumo

A aplicação das novas tecnologias à atividade agrícola, associada aos Sistemas de Posicionamento Global, gera elevada quantidade de informação georreferenciada. Deste modo, somos muitas vezes confrontados com atribuições distintas de sistemas de coordenadas. A transformação dos dados provenientes de uma das fontes de informação no sistema de coordenadas dos dados provenientes de outra fonte é uma etapa prévia e fundamental para qualquer análise de informação georreferenciada. Este trabalho tem como objetivo conhecer e entender o processo de transformação de coordenadas geográficas em retangulares e vice-versa, bem como a transformação entre sistemas de coordenadas distintos, através das ferramentas do software ArcMap por ser uma questão colocada frequentemente por alunos e outros utilizadores que tentam utilizar as ferramentas Sistemas de Informação Geográfica.

Palavras-chave: informação georreferenciada, transformação do sistema de coordenadas, agricultura de precisão

1. Introduction

The GPS (Global Positioning System) has a large area of applications whether on land, air or sea. In agriculture, the GPS in combination with geographic information systems (GIS) have been decisive to the development and implementation of precision farming system.

The access to global positioning technology allows to georeference the position of a given agricultural machine with a metric or submetric accuracy, depending on the type of GPS system used. Thus, the survey of georeferenced data makes it possible to control some production factors in an environmentally friendly way.

The global positioning system (GPS) receivers, used to locate and navigate agricultural vehicles within a field have become the most common sensors in precision agriculture (Adamchuk, 2005/2006). In this context, new technologies have made it possible to stop thinking about the agricultural parcel as a unit of homogeneous treatment to consider the parcel as a heterogeneous unit that varies in space. The characterization of the spatial variability of soil is only possible through the use of technologies that, combined with global positioning systems (GPS), allow to obtain, in an easy and economical way, a dense information on soil properties, as for instance the pH (e.g. Schirrmann et al.), electrical conductivity (e.g. Corwin and LESCH., 2005; Amin et al., 2004) and productivity (e.g. DIKER et al., 2004; Miao et al., 2006), which can then be correlated with more expensive soil attributes (Chig et al., 2010).

The accuracy GPS receivers allow to determinate geographic coordinates (latitude and longitude) and the high accuracy GPS allows measurement of altitude (elevation). In this way it is possible to calculate relevant parameters (e. g. slope (Cox et al., 2006);

6

flow direction (Marques da Silva and Silva, 2008)) to the terrain that influence the agriculture production (Adamchuk et al., 2004).

The acquisition of geo-referenced information allows, not only the identification of the spatial variability of the agricultural parcel, but also, site-specific management zones, with the application of fertilizers and pesticides as inputs only where they are needed, and when they are needed, contributing in the long term to the sustainability of agricultural production (Lowenberg and Bongiovanni, 2004).

Nevertheless, this management requires work with multiple layers of georeferenced information in order to develop the prescription maps successfully. The integration of data from different sources of information requires that data be processed or obtained in the same geographical referencing system.

However, some users have difficulties in entering georeferenced data into a geographic information system and in displaying them in a coordinated and appropriate projection system. In this paper, we demonstrate a set of illustrative steps of this process using maize yield data.

2. Materials, methods and procedures

This study was conducted using data collected from a single agricultural field, in Fronteira (Lat: +69.09607; Long: -7.611662), the Alentejo region of southern Portugal. The considered yield year was 2002 and maize was sown in late April/early May and harvested in September/October. A CLAAS Lexion 450 combine harvester was used, equipped with a combine electronic board information system (CEBIS), providing instantaneous yield and grain moisture data, with less than 5% error. The combine harvester was equipped with: a 4.5m cutting header; a differential GPS Pilot; a grain

4

mass flow sensor (through the impact force of grain hitting a plate) and a grain moisture sensor (by sensing the dielectric properties of the harvested grain), both near the top of the clean grain elevator. All these sensors were produced by CLAAS, Harsewinkel, Germany. The data were imported and manipulated in Microsoft Office Excel.

The SPSS[®] software (IBM SPSS Statistics, 2009) was used in the yield spatial data exploratory analysis to check the presence of global outliers and normality.

The yield data were analyzed using the software $\operatorname{ArcGIS}^{TM}$ (ESRI, 2009) which was used for the transformation of the coordinate system.

2.1. Creation of georeferenced shape

Production data from GPS CLAAS Lexion 450 combine harvester in geographic coordinate system (GWS84) and decimal degrees were imported into a Microsoft Excel File (Figure 1).

	А	В	С	D	E	F	G	E
1	LONG_CONV	LAT_CONV	MAIZE	TIME	SPEED	DATE	MOISTURE	
2	-7,619366	39,087835	2,538	143625,0	5,00	28.09.02	26,50	
3	-7,619366	39,087765	6,176	143630,0	5,10	28.09.02	26,50	
4	-7,619366	39,087695	1,341	143635,0	5,10	28.09.02	26,50	
5	-7,619366	39,087635	3,385	143640,0	5,20	28.09.02	26,50	
6	-7,619356	39,087545	6,270	143646,0	5,30	28.09.02	26,50	
7	-7,619356	39,087465	1,422	143651,0	5,00	28.09.02	26,50	
8	-7,619356	39,087395	0,529	143656,0	4,60	28.09.02	26,50	
9	-7,619336	39,087325	6,097	143701,0	4,60	28.09.02	26,50	
10	-7,619336	39,087265	9,202	143706,0	4,00	28.09.02	26,50	•
14 -								
Pro	Pronto 🔲 🛄 100% 🗩 🕂 🕂							

Figure 1. Excel table data.

The excel file data were added to ArcGis: ArcMap 9.6. Figures 2 and 6 show the necessary steps to transform the geographic coordinate system into a projected coordinate system.

	Display XY Data 🦹 🔀
	A table containing X and Y coordinate data can be added to the map as a layer
CoordinateSystem.mxd - ArcMap - ArcView	Choose a table from the map or browse for another table:
<u>File Edit View Bookmarks Insert Selection Tools Window</u>	'2002\$'
Editor ► Image: Create New Feature □ <t< th=""><th>Specify the fields for the X and Y coordinates: X Field: LONG_CONV Y Field: LAT_CONV</th></t<>	Specify the fields for the X and Y coordinates: X Field: LONG_CONV Y Field: LAT_CONV
□	Coordinate System of Input Coordinates Description: Unknown Coordinate System Show Details Edit Wam me if the resulting layer will have restricted functionality
	OK Cancel



Browse for Coordinate System Look in: Geographic Coordinate Systems Africa South America Antarctica Sphereid-based Asia Australia and New Zealand County Systems Europe North America Oceans Solar System Name: World Show of type: Coordinate Systems	Image: System Image: System Look in: Image: System Look in: Image: System Image: System	Display XY Data A table containing X and Y coordinate data can be addinate as a layer Choose a table from the map or browse for another table '2002S' Specify the fields for the X and Y coordinates: X Field: LONG_CONV Y Field: LAT_CONV Coordinate System of Input Coordinates Description: Geographic Coordinate System: Name: GCS_WGS_1384	P 23
Name: World Show of type: Coordinate Systems	MGS 1984.prj WGS 1984.prj TRF 1996.prj TRF 1997.prj Name: WGS 1984.prj Show of type: Coordinate Systems	Show Details Warn me if the resulting layer will have restricted fu	Edt Cancel

Figure 3. Allocation of the coordinate system.

After allocating the coordinate system you need to transform the data into shapefile.

In secondary menu select Data and Export Data (Figure 4).

🖃 🛃 coordinate system		Export Data
Grief C:\Users\Anabela\L	Jesktop\Coordinates\maize.xlsx	Export: All features
* .20025' ¥	Remove	Use the same coordinate system as:
	Open Attribute <u>T</u> able	C the data frame
	Joins and Relates	 the feature dataset you export the data into (only applies if you export to a feature dataset in a geodatabase)
4	Zoom To Layer	Output shapefile or feature class:
2	Zoom To <u>M</u> ake Visible	C:\Users\Anabela\Desktop\Coordinates\maize_WGS84.shp
_	Visible Scale Range	
	Us <u>e</u> Symbol Levels	
	Selection	OK Cancel
	Label Features	
	Convert Labels to Annotation	1
	Convert Features to Graphics	
_	Convert Symbology to Representation	
	<u>D</u> ata ►	<u>R</u> epair Data Source
	Save As Lager File	<u>E</u> xport Data
	Propert <u>i</u> es	<u>M</u> ake Permanent
		View Metadata

Figure 4. Data export in the chosen coordinate system.

2.2. Geographic data transformation

The earth as a sphere or a spheroid and its three-dimensional surface must be projected to create a flat map sheet.

In ArcToolBox select Data Management Tools and Projections and Transformations.

Choose the coordinate system in which you will work, according to the coordinate

system where the remaining layers of the project work are.

Real AssTaulhau				
	Project			
3D Analyst Tools				
Analysis Tools	Input Dataset or Feature Class			
Cartography Tools	maize_WGS84 💌 🗃			
🔁 🚳 Conversion Tools	Input Coordinate System (optional)			
🔁 🥸 Data Interoperability Tools	GCS_WGS_1984			
🖨 🚳 Data Management Tools	Output Dataset or Feature Class			
🛱 🕸 Data Comparison	C:\Users\Anabela\Desktop\Coordinates\maize military			
🕀 🔕 Database	Output Coordinate System			
🕀 🥸 Domains	Lisboa Hayford Gauss IGeoF			
🕀 🚳 Feature Class	Geographic Transformation (optional)			
🕀 💩 Features				
🕀 🔕 Fields				
🕀 💩 File Geodatabase				
🕀 🔕 General 🗧				
🕀 💩 Generalization	X -			
🗊 🔕 Indexes	OK Cancel Environments Show Hen >>			
🕀 💩 Joins				
The State of the second				
Projections and Transformations				
Feature				
Batch Project				
Create Spatial Reference				
Project				
	Spatial Reference Properties			
Browse for Coordinate System	3 Xi Coordinate System			
Look in: 🞯 Coordinate Systems	Name: Lisboa_Hayford_Gauss_IGeoE			
	- Detaile			
Geographic Coordinate Systems	Decision Tennyana Manatar			
Projected Coordinate Systems	False_Easting: 200000,000000			
	False_Northing: 300000,000000 Central_Meridian: -8 131906			
Browse for Coordinate System	Scale_Factor: 1,000000			
	Linear Unit: Meter (1,000000)			
Look in: National Grids 🗾 🔁	Geographic Coordinate Sustan: GCS Datum Linhoa Hauford			
🕲 Kuwait Oil Co - Lambert.prj 🖉	Lisboa Hayford Gauss Angular Unit: Degree (0.017453292519943299)			
🕲 Kuwait Utility KTM.prj	Lisboa Hayford Gauss Prime Meridian: Greenwich (0,00000000000000000000) Datum: D. Datum, Lisboa, Hayford			
🕲 Lake Maracaibo Grid.prj	LKS 1992 Latvia TM.prj Spheroid: International_1924 -			
Cake Maracaibo Grid M1.prj	LKS 1992 Latvia TM (FI			
Warne: W Lake Maracaibo Grid M3.prj	LKS 1994 Lithuania IM Select Select a predefined coordinate system.			
Show of type: Coordinate S @ Le Pouce 1934 Mauritius Grid.pri	Insport a coordinate system and X/Y, Z and M Insport domains from an existing geodataset (e.g.,			
Lietuvos Koordinaciu Sistema.prj	Madrid 1870 Madrid St			
🖉 Lisboa Bessel Bonne.prj	MAGNA Ciudad Bogot Create a new coordinate system.			
	Edit the properties of the currently selected			
	coordinate system.			
Name: Lisboa Hayford Gauss IGeoE.prj	. Clear Sets the coordinate system to Unknown.			
Show of type: Coordinate Systems	C Save As Save the coordinate system to a file.			

Figure 5. ArcToolbox and transformation of data into projected coordinate system.

3. Results and discussion

From a brief set of steps available in Arcgis 9.6 tools, geographical coordinates of data,

obtained by a GPS receiver, were transformed into a common projected coordinate

system. We can see the maize yield data in GWS84 system (Figure 6 (a)) and maize yield data in Hayford Gauss Lisbon IGeoE system (Figure 6 (b)), the same used in the remaining working layers.



Figure 7. Maize Yield data shapefiles with a different coordinate system:

(a) WGS84; (b) Hayford Gauss Lisbon IGeoE

4. Conclusions

Currently geographic information tools are useful in many areas of knowledge being essential in precision agriculture.

The procedure makes it possible: (i) to distribute spatially the points of yield maize in the correct position; (ii) to transform the original geographic coordinate system into another coordinate system project within a common geographic framework.

Acknowledgements

The authors are very grateful to Eng. Castro Duarte for all his material and immaterial support.

References

- Adamchuk, V. I. (2005/2006). Characterizing Soil Variability Using On-the-Go Sensing Technology. Site-Specific Management Guidelines SSMG-44. Norcross, Georgia: Potash and Phosphate Institute.
- Adamchuk, V.I.; Hummel, J.W.; Morgan, M.T. and Upadhyaya, S.K.(2004). On-the-go soil sensors for precision agriculture. *Comput. Electron. Agric.*, 44, 71–91.
- Amin, M.S.M.; Aimrun, W.; Eltaib, S.M. and Chan, C.S. (2004). Spatial soil variability mapping using electrical conductivity sensor for precision farming of rice. *Int. J. Engin. Technol.*, 1 (1), 47 – 57.
- Bongiovanni, R. and Lowenberg-Deboer, J. (2004). Precision agriculture and sustainability. *Precis. Agric.*, 5(4), 659-687.
- Chig, L. A.; Couto, E. G. and Amorim, R. S. S. (2010). Tecnologias para levantamento da variabilidade dos atributos do solo para um programa de agricultura de precisão. UNICiências, 14 (2).
- Corwin, D.L. and Lesch, S.M. (2005). Characterizing soil spatial variability with apparent soil electrical conductivity.I. Survey protocols. *Comput. Electron. Agric.*, 46, 106–166.

- Cox, M. S.; Gerard, P. D. ; Wardlaw, M. C. and Abshire, M. J. (2006). Variability of Selected Soil Properties and Their Relationships with Soybean Yield. *Soil Sci. Soc. Am.* J. 67, 1296–1602.
- Diker, K; Heermann, D. F. e Brodahl, M. K. (2004). Frequency Analysis of Yield for Delineating Yield Response Zones. *Precis. Agric.*, 5, 465–444.
- ESRI (2009). ARCGIS 9.6.6. Redlands, CA, USA: Environmental Systems Research Institute.
- ESRI (1999). Environmental Systems Research Institute Inc.Building a Geodatabase. http://downloads.esri.com/support/documentation/ao_/1005Building_a_Geoda tabase.pdf.
- ESRI (2014). ArcGIS Desktop Help 9.6. An overview of the Projections and Transformations toolset.

http://webhelp.esri.com/arcgisdesktop/9.6/index.cfm?TopicName=An%20overvi ew%20of%20the%20Projections%20and%20Transformations%20toolset.

Accessed 10 January 2014.

- Gonçalves, J. (2008). Adopção de Sistemas de Referenciação Geográfica Globais. ESIG2008.
- Marques da Silva, J.R e Silva, L.L. (2008). Evaluation of the relationship between maize yield spatial and temporal variability and different topographic attributes. *Biosyst. Eng.*, 101, 186-190.
- Miao, Y.; Mulla, D. J. and Robert, P. C. (2006). Spatial variability of soil properties, corn quality and yield in two Illinois, USA fields: implications for precision corn management. *Precis. Agric*, 7, 5–20.

Schirrmann, M.; Gebbers, R.; Kramer, E. and Seidel, J. (2011). Soil pH Mapping with an

On-The-Go Sensor. Sensors, 11, 576-598; doi:10.6690/s110100576